

TCB

GRANT OF EQUIPMENT
AUTHORIZATION

TCB

Certification

Issued Under the Authority of the
Federal Communications Commission

By:

Siemic Inc.
775 Montague Expressway
Milpitas, CA 95035

Date of Grant: 03/13/2017

Application Dated: 03/13/2017

ASUSTeK Computer Inc
4F, No. 150, Li-Te Rd.
Peitou, Taipei, 112
Taiwan

Attention: Jackson Yen , Associate Vice President

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is
VALID ONLY for the equipment identified hereon for use under the Commission's
Rules and Regulations listed below.FCC IDENTIFIER: MSQA002
Name of Grantee: ASUSTeK Computer Inc
Equipment Class: PCS Licensed Transmitter held to ear
Notes: ASUS Phone

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
HC	22H	824.2 - 848.8	0.904	0.005 PM	249KGXW
	22H	824.2 - 848.8	0.258	0.005 PM	247KG7W
HC	22H	826.4 - 846.6	0.115	0.005 PM	4M16F9W
	22H	824.7 - 848.3	0.102	0.005 PM	1M09G7D
	22H	824.7 - 848.3	0.081	0.005 PM	1M09W7D
	22H	825.5 - 847.5	0.101	0.005 PM	2M70G7D
	22H	825.5 - 847.5	0.081	0.005 PM	2M70W7D
	22H	826.5 - 846.5	0.101	0.005 PM	4M49G7D
	22H	826.5 - 846.5	0.082	0.005 PM	4M49W7D
	22H	829.0 - 844.0	0.102	0.005 PM	8M98G7D
	22H	829.0 - 844.0	0.081	0.005 PM	8M98W7D
HC	24E	1850.2 - 1909.8	0.8	0.002 PM	248KGXW
	24E	1850.2 - 1909.8	0.322	0.002 PM	249KG7W
HC	24E	1852.4 - 1907.6	0.181	0.002 PM	4M17F9W
	24E	1850.7 - 1909.3	0.203	0.002 PM	1M09G7D
	24E	1850.7 - 1909.3	0.162	0.002 PM	1M09W7D
	24E	1851.5 - 1908.5	0.202	0.002 PM	2M70G7D
	24E	1851.5 - 1908.5	0.161	0.002 PM	2M70W7D
	24E	1852.5 - 1907.5	0.203	0.002 PM	4M49G7D
	24E	1852.5 - 1907.5	0.161	0.002 PM	4M49W7D
	24E	1855.0 - 1905.0	0.203	0.002 PM	8M97G7D
	24E	1855.0 - 1905.0	0.161	0.002 PM	8M97W7D
	24E	1857.5 - 1902.5	0.203	0.002 PM	13M5G7D
	24E	1857.5 - 1902.5	0.161	0.002 PM	13M5W7D
	24E	1860.0 - 1900.0	0.204	0.002 PM	18M0G7D
	24E	1860.0 - 1900.0	0.161	0.002 PM	18M0W7D

HC	27	1712.4 - 1752.6	0.203	0.002	PM	4M16F9W
	27	1710.7 - 1754.3	0.203	0.002	PM	1M09G7D
	27	1710.7 - 1754.3	0.161	0.002	PM	1M09W7D
	27	1711.5 - 1753.5	0.203	0.002	PM	2M70G7D
	27	1711.5 - 1753.5	0.161	0.002	PM	2M70W7D
	27	1712.5 - 1752.5	0.204	0.002	PM	4M49G7D
	27	1712.5 - 1752.5	0.16	0.002	PM	4M49W7D
	27	1715.0 - 1750.0	0.203	0.002	PM	8M98G7D
	27	1715.0 - 1750.0	0.165	0.002	PM	8M98W7D
	27	1717.5 - 1747.5	0.203	0.002	PM	13M5G7D
	27	1717.5 - 1747.5	0.162	0.002	PM	13M5W7D
	27	1720.0 - 1745.0	0.205	0.002	PM	18M1G7D
	27	1720.0 - 1745.0	0.161	0.002	PM	18M1W7D
	27	699.7 - 715.3	0.114	0.006	PM	1M09G7D
	27	699.7 - 715.3	0.089	0.006	PM	1M09W7D
	27	700.5 - 714.5	0.115	0.005	PM	2M71G7D
	27	700.5 - 714.5	0.09	0.005	PM	2M70W7D
	27	701.5 - 713.5	0.114	0.006	PM	4M50G7D
	27	701.5 - 713.5	0.09	0.006	PM	4M50W7D
	27	704.4 - 711.0	0.113	0.005	PM	9M00G7D
	27	704.4 - 711.0	0.091	0.005	PM	9M00W7D
	27	779.5 - 784.5	0.114	0.005	PM	4M51G7D
	27	779.5 - 784.5	0.091	0.005	PM	4M50W7D
	27	782.0 - 782.0	0.114	0.005	PM	8M93G7D
	27	782.0 - 782.0	0.09	0.005	PM	8M93W7D
	27	2502.5 - 2567.5	0.165	0.0016	PM	4M49G7D
	27	2502.5 - 2567.5	0.13	0.0016	PM	4M49W7D
	27	2505.0 - 2565.0	0.162	0.0015	PM	8M97G7D
	27	2505.0 - 2565.0	0.13	0.0015	PM	8M97W7D
	27	2507.5 - 2562.5	0.167	0.0016	PM	13M5G7D
	27	2507.5 - 2562.5	0.129	0.0016	PM	13M5W7D
	27	2510.0 - 2560.0	0.162	0.0014	PM	18M0G7D
	27	2510.0 - 2560.0	0.127	0.0014	PM	18M0W7D

Output power listed is ERP/EIRP. For body worn operation, this phone has been tested and meets FCC RF exposure guidelines when used with an accessory that contains no metal and that positions the handset a minimum of 15 mm from the body. Use of other accessories may not ensure compliance with FCC RF exposure guidelines. Highest reported SAR for Head, Body-worn accessory, hotspot and simultaneous transmission is : 0.25 W/kg, 0.61 W/kg, 1.19 W/kg and 1.41 W/kg respectively. HAC rating is M4T4-2011

HC: This equipment complies with the hearing aid compatibility technical requirements of Section 20.19 of the rules.