

## MAXIMUS VIII HERO

### DDR4 3866 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
<b>G.SKILL</b>	F4-3866C18D-8GTZ	8GB (2 x 4GB)	SS	-	-	18-22-22-42	1.35V	●	
<b>Team</b>	TCD44G3866C18BBK	8GB (2 x 4GB)	SS	-	-	18-20-20-40	1.35V	●	

\*When running XMP at DDR4 3200 MHz or higher, the system's stability depends on the CPU's capabilities.

### DDR4 3800 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
<b>AVEXIR</b>	AVD4UZ138001804G-2CIR	8GB (2 x 4GB)	SS	-	-	18-20-20-40	1.35V	●	
<b>AVEXIR</b>	AVD4UZ138001804G-2BZ1	8GB (2 x 4GB)	SS	-	-	18-20-20-40	1.35V	●	
<b>G.SKILL</b>	F4-3800C18D-8GTZ	8GB (2 x 4GB)	SS	-	-	18-20-20-38	1.35V	●	

\*When running XMP at DDR4 3200 MHz or higher, the system's stability depends on the CPU's capabilities.

### DDR4 3733 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
<b>ADATA</b>	AX4U3733W4G17-DWZ	8GB (2 x 4GB)	SS	-	-	17-18-18-38	1.35V	●	
<b>AVEXIR</b>	AVD4UZ137331804G-2CIR/BZ1	8GB (2 x 4GB)	SS	-	-	18-20-20-40	1.35V	●	
<b>AVEXIR</b>	AVD4UZ137331804G-4CIR/BZ1	16GB (4 x 4GB)	SS	-	-	18-20-20-40	1.35V	●	●
<b>G.SKILL</b>	F4-3733C17D-8GVK	8GB (2 x 4GB)	SS	-	-	17-19-19-39	1.35V	●	
<b>G.SKILL</b>	F4-3733C17D-8GTZ	8GB (2 x 4GB)	SS	-	-	17-19-19-39	1.35V	●	
<b>G.SKILL</b>	F4-3733C17Q-16GVK	16GB (4 x 4GB)	SS	-	-	17-19-19-39	1.35V	●	●
<b>G.SKILL</b>	F4-3733C17Q-16GTZ	16GB (4 x 4GB)	SS	-	-	17-19-19-39	1.35V	●	●

\*When running XMP at DDR4 3200 MHz or higher, the system's stability depends on the CPU's capabilities.

### DDR4 3733 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
<b>ADATA</b>	AX4U3700W4G17-DWZ	8GB (2 x 4GB)	SS	-	-	17-18-18-38	1.35V	●	
<b>ADATA</b>	AX4U3700W4G17-QWZ	16GB (4 x 4GB)	SS	-	-	17-18-18-38	1.35V	●	●

\*When running XMP at DDR4 3200 MHz or higher, the system's stability depends on the CPU's capabilities.

### DDR4 3600 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
<b>ADATA</b>	AX4U3600W4G17-DWZ	8GB (2 x 4GB)	SS	-	-	17-18-18-38	1.35V	●	
<b>ADATA</b>	AX4U3600W4G17-QWZ	16GB (4 x 4GB)	SS	-	-	17-18-18-38	1.35V	●	●
<b>APACER</b>	78.BAGN2.4020B	8GB (2 x 4GB)	SS	-	-	18-18-18-42	1.35V	●	
<b>AVEXIR</b>	AVD4UZ136001804G-2CIR/BZ1	8GB (2 x 4GB)	SS	-	-	18-20-20-40	1.35V	●	
<b>AVEXIR</b>	AVD4UZ136001804G-4CIR/BZ1	16GB (4 x 4GB)	SS	-	-	18-20-20-40	1.35V	●	●
<b>CORSAIR</b>	CMD16GX4M4B3600C18	16GB (4 x 4GB)	SS	-	-	18-19-19-38	1.35V	●	●
<b>CORSAIR</b>	CMK32GX4M4B3600C18	32GB (4 x 8GB)	SS	-	-	18-19-19-39	1.35V	●	●
<b>CORSAIR</b>	CMK8GX4M2B3600C18	8GB (2 x 4GB)	SS	-	-	18-19-19-39	1.35V	●	
<b>G.SKILL</b>	F4-3600C17-8GVK	8GB (2 x 4GB)	SS	-	-	17-18-18-38	1.35V	●	
<b>G.SKILL</b>	F4-3600C17-8GTZ	8GB (2 x 4GB)	SS	-	-	17-18-18-38	1.35V	●	

<b>G.SKILL</b>	F4-3600C17Q-16GTZ	16GB (4 x 4GB)	SS	-	-	17-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3600C17-16GVK	16GB (4 x 4GB)	SS	-	-	17-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3600C17-16CGTZ	16GB (4 x 4GB)	SS	-	-	17-18-18-38	1.35V	●	●
<b>Team</b>	TXD416G3600HC18ADC01	16GB (2 x 8GB)	SS	-	-	18-20-20-39	1.35V	●	●
<b>Team</b>	TXWD416G3600HC18ADC01	16GB (2 x 8GB)	SS	-	-	18-20-20-39	1.35V	●	●

\*When running XMP at DDR4 3200 MHz or higher, the system's stability depends on the CPU's capabilities.

#### DDR4 3500 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
<b>G.SKILL</b>	F4-3500C17Q-16GRRD	16GB (4 x 4GB)	SS	-	-	17-18-18-36	1.35V	●	●

\*When running XMP at DDR4 3200 MHz or higher, the system's stability depends on the CPU's capabilities.

#### DDR4 3466 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
<b>ADATA</b>	AX4U3466W4G16-DWZ	8GB (2 x 4GB)	SS	-	-	16-17-17-36	1.35V	●	●
<b>ADATA</b>	AX4U3466W4G16-QWZ	16GB (4 x 4GB)	SS	-	-	16-17-17-36	1.35V	●	●
<b>APACER</b>	78.BAGN1.4020B	8GB (2 x 4GB)	SS	-	-	18-18-18-42	1.35V	●	●
<b>AVEXIR</b>	AVD4UZ134661704G-2CIR/BZ1	8GB (2 x 4GB)	SS	-	-	17-18-18-38	1.35V	●	●
<b>AVEXIR</b>	AVD4UZ134661704G-4CIR/BZ1	16GB (4 x 4GB)	SS	-	-	17-18-18-38	1.35V	●	●
<b>CORSAIR</b>	CMD16GX4M4B3466C18	16GB (4 x 4GB)	SS	-	-	18-19-19-38	1.35V	●	●
<b>CORSAIR</b>	CMK32GX4M4B3466C16	32GB (4 x 8GB)	SS	-	-	16-18-18-36	1.35V	●	●
<b>CORSAIR</b>	CMK16GX4M2B3466C16	16GB (8 x 2GB)	SS	-	-	16-18-18-36	1.35V	●	●
<b>G.SKILL</b>	F4-3466C16Q-16GVK	16GB (4 x 4GB)	SS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3466C16Q-16GRRD	16GB (4 x 4GB)	SS	-	-	16-18-18-38	1.35V	●	●
<b>Team</b>	TCD48G3466C17ABK	16GB (2 x 8GB)	SS	-	-	17-19-19-39	1.35V	●	●

\*When running XMP at DDR4 3200 MHz or higher, the system's stability depends on the CPU's capabilities.

#### DDR4 3400 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
<b>ADATA</b>	AX4U3400W4G16-DWZ	8GB (2 x 4GB)	SS	-	-	16-17-17-36	1.35V	●	●
<b>ADATA</b>	AX4U3400W4G16-QWZ	16GB (4 x 4GB)	SS	-	-	16-17-17-36	1.35V	●	●
<b>CORSAIR</b>	CMK16GX4M4B3400C16	16GB (4 x 4GB)	SS	-	-	16-18-18-40	1.35V	●	●
<b>G.SKILL</b>	F4-3400C16Q-16GRKD	16GB (4 x 4GB)	SS	-	-	16-16-16-36	1.35V	●	●
<b>G.SKILL</b>	F4-3400C16Q-16GRBD	16GB (4 x 4GB)	SS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3400C16D-16GRK	16GB (2 x 8GB)	DS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3400C16D-16GVK	16GB (2 x 8GB)	DS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3400C16D-16GTZ	16GB (2 x 8GB)	DS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3400C16Q-32GRK	32GB (4 x 8GB)	DS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3400C16Q-32GVK	32GB (4 x 8GB)	DS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3400C16Q-32GTZ	32GB (4 x 8GB)	DS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3400C16D-32GRK	32GB (2 x 16GB)	DS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3400C16D-32GVK	32GB (2 x 16GB)	DS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3400C16D-32GTZ	32GB (2 x 16GB)	DS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3400C16Q-64GRK	64GB (4 x 16GB)	DS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3400C16Q-64GVK	64GB (4 x 16GB)	DS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3400C16Q-64GTZ	64GB (4 x 16GB)	DS	-	-	16-18-18-38	1.35V	●	●

\*When running XMP at DDR4 3200 MHz or higher, the system's stability depends on the CPU's capabilities.

### DDR4 3333 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
<b>ADATA</b>	AX4U3333W4G16-DRZ	8GB (2 x 4GB)	SS	-	-	16-16-16-36	1.35V	●	
<b>ADATA</b>	AX4U3333W4G16-QRZ	16GB (4 x 4GB)	SS	-	-	16-16-16-36	1.35V	●	●
<b>AVEXIR</b>	AVD4UZ133331604G-2CIR/BZ1	8GB (2 x 4GB)	SS	-	-	16-18-18-38	1.35V	●	
<b>AVEXIR</b>	AVD4UZ133331604G-4CIR/BZ1	16GB (4 x 4GB)	SS	-	-	16-18-18-38	1.35V	●	●
<b>CORSAIR</b>	CMD16GX4M4B3333C16	16GB (4 x 4GB)	SS	-	-	16-18-18-36	1.35V	●	●
<b>CORSAIR</b>	CMK64GX4M4B3333C16	16GB(4GB*4)	DS	-	-	16-18-18-36	1.35V		●
<b>G.SKILL</b>	F4-3333C16Q-16GRRD	16GB (4 x 4GB)	SS	-	-	16-18-18-38	1.35V	●	●

\*When running XMP at DDR4 3200 MHz or higher, the system's stability depends on the CPU's capabilities.

### DDR4 3300 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
<b>ADATA</b>	AX4U3300W4G16-DRZ	8GB (2 x 4GB)	SS	-	-	16-16-16-36	1.35V	●	
<b>ADATA</b>	AX4U3300W4G16-QRZ	16GB (4 x 4GB)	SS	-	-	16-16-16-36	1.35V	●	●
<b>AVEXIR</b>	AVD4U33001604G-4CIR	16GB (4 x 4GB)	SS	-	-	16-18-18-36	1.35V	●	●
<b>CORSAIR</b>	CMD16GX4M4B3300C16	16GB (4 x 4GB)	SS	-	-	16-18-18-36	1.35V	●	●
<b>CORSAIR</b>	CMK16GX4M4B3300C16	16GB (4 x 4GB)	SS	-	-	16-18-18-36	1.35V	●	●
<b>G.SKILL</b>	F4-3300C16Q-16GRKD	16GB (4 x 4GB)	SS	-	-	16-16-16-36	1.35V	●	●
<b>G.SKILL</b>	F4-3300C16Q-16GRK	16GB (4 x 4GB)	SS	-	-	16-16-16-36	1.35V	●	●

\*When running XMP at DDR4 3200 MHz or higher, the system's stability depends on the CPU's capabilities.

### DDR4 3200 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
<b>AVEXIR</b>	AVD4U32001604G-4CIR	16GB (4 x 4GB)	SS	-	-	16-18-18-36	1.35V	●	●
<b>ADATA</b>	AX4U3200W4G16-DRZ	8GB (2 x 4GB)	SS	-	-	16-16-16-36	1.35V	●	
<b>ADATA</b>	AX4U3200W4G16-QRZ	16GB (4 x 4GB)	SS	-	-	16-16-16-36	1.35V	●	●
<b>CORSAIR</b>	CMK16GX4M4B3200C15	16GB (4 x 4GB)	SS	-	-	15-17-17-35	1.35V	●	●
<b>CORSAIR</b>	CMD16GX4M4B3200C16	16GB (4 x 4GB)	SS	-	-	16-18-18-36	1.35V	●	●
<b>CORSAIR</b>	CMD16GX4M4C3200C15	16GB(4GB*4)	SS	-	-	15-17-17-35	1.35V		●
<b>CORSAIR</b>	CMK8GX4M2B3200C16	8GB(4GB*2)	SS	-	-	16-18-18-36	1.35V	●	
<b>CORSAIR</b>	CMK16GX4M4C3200C16	16GB(4GB*4)	SS	-	-	16-18-18-36	1.35V		●
<b>CORSAIR</b>	CMK32GX4M4B3200C16	32GB (4 x 8GB)	DS	-	-	16-18-18-36	1.35V	●	●
<b>Kingston</b>	HX432C16PBK4/16	16GB (4 x 4GB)	SS	-	-	16-16-16-39	1.35V	●	●
<b>G.SKILL</b>	F4-3200C16Q-16GVR	16GB (4 x 4GB)	SS	-	-	16-16-16-36	1.35V	●	●
<b>G.SKILL</b>	F4-3200C16Q-16GRKD	16GB (4 x 4GB)	SS	-	-	16-16-16-36	1.35V	●	●
<b>G.SKILL</b>	F4-3200C16D-16GRK	16GB (2 x 8GB)	DS	-	-	16-16-16-36	1.35V	●	
<b>G.SKILL</b>	F4-3200C16D-16GVK	16GB (2 x 8GB)	DS	-	-	16-16-16-36	1.35V	●	
<b>G.SKILL</b>	F4-3200C16D-16GTZ	16GB (2 x 8GB)	DS	-	-	16-16-16-36	1.35V	●	
<b>G.SKILL</b>	F4-3200C16Q-32GVR	32GB (4 x 8GB)	DS	-	-	16-16-16-36	1.35V	●	●
<b>G.SKILL</b>	F4-3200C16Q-32GRK	32GB (4 x 8GB)	DS	-	-	16-16-16-36	1.35V	●	●
<b>G.SKILL</b>	F4-3200C16Q-32GVK	32GB (4 x 8GB)	DS	-	-	16-16-16-36	1.35V	●	●
<b>G.SKILL</b>	F4-3200C16Q-32GTZ	32GB (4 x 8GB)	DS	-	-	16-16-16-36	1.35V	●	●
<b>G.SKILL</b>	F4-3200C15D-32GRK	32GB (2 x 16GB)	DS	-	-	15-15-15-35	1.35V	●	
<b>G.SKILL</b>	F4-3200C15D-32GVK	32GB (2 x 16GB)	DS	-	-	15-15-15-35	1.35V	●	
<b>G.SKILL</b>	F4-3200C15D-32GTZ	32GB (2 x 16GB)	DS	-	-	15-15-15-35	1.35V	●	

<b>G.SKILL</b>	F4-3200C16D-32GRK	32GB (2 x 16GB)	DS	-	-	16-18-18-38	1.35V	●	
<b>G.SKILL</b>	F4-3200C16D-32GVK	32GB (2 x 16GB)	DS	-	-	16-18-18-38	1.35V	●	
<b>G.SKILL</b>	F4-3200C16D-32GTZ	32GB (2 x 16GB)	DS	-	-	16-18-18-38	1.35V	●	
<b>G.SKILL</b>	F4-3200C16Q-64GRK	64GB (4 x 64GB)	DS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3200C16Q-64GVK	64GB (4 x 64GB)	DS	-	-	16-18-18-38	1.35V	●	●
<b>G.SKILL</b>	F4-3200C16Q-64GTZ	64GB (4 x 64GB)	DS	-	-	16-18-18-38	1.35V	●	●

\*When running XMP at DDR4 3200 MHz or higher, the system's stability depends on the CPU's capabilities.

#### DDR4 3000 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
<b>ADATA</b>	AX4U3000W4G16-DRZ	8GB (2 x 4GB)	SS	-	-	16-16-16-36	1.35V	●	
<b>ADATA</b>	AX4U3000W4G16-QRZ	16GB (4 x 4GB)	SS	-	-	16-16-16-36	1.35V	●	●
<b>AVEXIR</b>	AVD4U30001504G-4CIR	16GB (4 x 4GB)	SS	-	-	15-15-15-35	1.35V	●	●
<b>CORSAIR</b>	CMD16GX4M4B3000C14	16GB (4 x 4GB)	SS	-	-	14-16-16-35	1.35V	●	●
<b>CORSAIR</b>	CMD16GX4M4B3000C15	16GB (4 x 4GB)	SS	-	-	15-17-17-35	1.35V	●	●
<b>CORSAIR</b>	CMK32GX4M4B3000C15	32GB (4 x 8GB)	DS	-	-	15-17-17-35	1.35V	●	●
<b>CORSAIR</b>	CMK8GX4M2B3000C15	8GB(4GB*2)	SS	-	-	15-17-17-35	1.35V	●	
<b>CORSAIR</b>	CMK64GX4M4B3000C15	64GB(16GB*4)	DS	-	-	15-17-17-35	1.35V		●
<b>CORSAIR</b>	CMK16GX4M2B3000C15	16GB(8GB*2)	DS	-	-	15-17-17-35	1.35V	●	
<b>Kingston</b>	HX430C15PB2k4/16	16GB (4 x 4GB)	SS	-	-	15-16-16-39	1.35V	●	●
<b>Kingston</b>	HX430C15PB2k2/16	8GB (2 x 4GB)	DS	-	-	15-16-16-39	1.35V	●	
<b>G.SKILL</b>	F4-3000C15Q-16GVR	16GB (4 x 4GB)	SS	-	-	15-15-15-35	1.35V	●	●
<b>G.SKILL</b>	F4-3000C15Q-16GRR	16GB (4 x 4GB)	SS	-	-	15-15-15-35	1.35V	●	●
<b>G.SKILL</b>	F4-3000C15Q-16GRK	16GB (4 x 4GB)	SS	-	-	15-15-15-35	1.35V	●	●
<b>G.SKILL</b>	F4-3000C15D-16GRK	16GB (2 x 8GB)	DS	-	-	15-15-15-35	1.35V	●	
<b>G.SKILL</b>	F4-3000C15D-16GVK	16GB (2 x 8GB)	DS	-	-	15-15-15-35	1.35V	●	
<b>G.SKILL</b>	F4-3000C15D-16GTZ	16GB (2 x 8GB)	DS	-	-	15-15-15-35	1.35V	●	
<b>G.SKILL</b>	F4-3000C15Q-32GVR	32GB (4 x 8GB)	DS	-	-	15-15-15-35	1.35V	●	●
<b>G.SKILL</b>	F4-3000C15Q-32GRK	32GB (4 x 8GB)	DS	-	-	15-15-15-35	1.35V	●	●
<b>G.SKILL</b>	F4-3000C15Q-32GVK	32GB (4 x 8GB)	DS	-	-	15-15-15-35	1.35V	●	●
<b>G.SKILL</b>	F4-3000C15Q-32GTZ	32GB (4 x 8GB)	DS	-	-	15-15-15-35	1.35V	●	●
<b>G.SKILL</b>	F4-3000C15D-32GRK	32GB (2 x 16GB)	DS	-	-	15-15-15-35	1.35V	●	
<b>G.SKILL</b>	F4-3000C15D-32GVK	32GB (2 x 16GB)	DS	-	-	15-15-15-35	1.35V	●	
<b>G.SKILL</b>	F4-3000C15D-32GTZ	32GB (2 x 16GB)	DS	-	-	15-15-15-35	1.35V	●	
<b>G.SKILL</b>	F4-3000C15Q-64GVR	64GB (4 x 16GB)	DS	-	-	15-15-15-35	1.35V	●	●
<b>G.SKILL</b>	F4-3000C15Q-64GRK	64GB (4 x 16GB)	DS	-	-	15-15-15-35	1.35V	●	●
<b>G.SKILL</b>	F4-3000C15Q-64GVK	64GB (4 x 16GB)	DS	-	-	15-15-15-35	1.35V	●	●
<b>G.SKILL</b>	F4-3000C15Q-64GTZ	64GB (4 x 16GB)	DS	-	-	15-15-15-35	1.35V	●	●

#### DDR4 2800 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
<b>ADATA</b>	AX4U2800W4G17	32GB ( 8x 4GB )	DS	-	-	17-17-17-36	1.2V	●	●
<b>ADATA</b>	AX4U2800W8G17	8GB	DS	-	-	15-15-15-36	1.2V	●	●
<b>Apacer</b>	78.BAGM8.AF20B(XMP)	4GB	SS	-	-	17-17-17-36	-	●	●
<b>Apacer</b>	78.CAGM8.AF30B(XMP)	8GB	DS	-	-	17-17-17-36	-	●	●
<b>AVEXIR</b>	AVD4U28001504G-4CIR(XMP)	4GB	SS	-	-	15-15-15-35	1.35V	●	●
<b>AVEXIR</b>	AVD4U28001608G-4CIR(XMP)	32GB ( 8x 4GB )	DS	-	-	16-16-16-36	1.2V	●	●

<b>CORSAIR</b>	CMD16GX4M4A2800C16(Ver4.23)(XMP)	16GB ( 4x 4GB )	SS	-	-	16-18-18-36	1.2V	•	•
<b>CORSAIR</b>	CMD16GX4M4A2800C16(Ver5.29)	16GB ( 4x 4GB )	SS	-	-	16-18-18-36	1.2V	•	•
<b>CORSAIR</b>	CMD32GX4M4A2800C16(Ver5.29)(XMP)	32GB ( 4x 8GB )	DS	-	-	18-18-18-36	1.2V	•	•
<b>CORSAIR</b>	CMK16GX4M4A2800C16(Ver4.23)(XMP)	16GB ( 4x 4GB )	SS	-	-	16-16-18-36	1.2V	•	•
<b>CORSAIR</b>	CMK16GX4M4A2800C16(Ver5.29)	16GB ( 4x 4GB )	SS	-	-	16-18-18-36	1.2V	•	•
<b>CORSAIR</b>	CMK32GX4M4A2800C16(Ver5.29)(XMP)	32GB ( 4x 8GB )	DS	-	-	16-18-18-36	1.2V	•	•
<b>G.SKILL</b>	F4-2800C15Q2-64GRK(XMP)	64GB ( 8x 8GB )	DS	-	-	15-16-16-35	1.25V	•	•
<b>G.SKILL</b>	F4-2800C16Q-16GRR(XMP)	16GB ( 4x 4GB )	SS	-	-	16-16-16-36	1.2V	•	•
<b>G.SKILL</b>	F4-2800C16Q-32GRR(XMP)	32GB ( 4x 8GB )	DS	-	-	16-16-16-36	1.2V	•	•
<b>Kingston</b>	HX428C14PBK4/16(XMP)	16GB ( 4x 4GB )	SS	-	-	14-15-15-40-2	1.35V	•	•
<b>Panram</b>	PUD42800C164G4NJW(XMP)	16GB ( 4x 4GB )	SS	-	-	16-18-18-36	1.25V	•	•

### DDR4 2666 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
<b>AVEXIR</b>	AVD4U26661504G-4CIR(XMP)	4GB	SS	-	-	15-15-15-35	1.2V		•
<b>AVEXIR</b>	AVD4U26661608G-4CIR(XMP)	32GB ( 8x 4GB )	DS	-	-	16-16-16-36	1.2V		•
<b>CORSAIR</b>	CMD16GX4M4A2666C15(Ver4.23)(XMP)	16GB ( 4x 4GB )	SS	-	-	15-17-17-35	1.2V	•	•
<b>CORSAIR</b>	CMD16GX4M4A2666C16(Ver4.23)(XMP)	16GB ( 4x 4GB )	SS	-	-	16-18-18-35	1.2V	•	•
<b>CORSAIR</b>	CMD16GX4M4A2666C16(Ver5.29)(XMP)	16GB ( 4x 4GB )	SS	-	-	16-18-18-35	1.2V	•	•
<b>CORSAIR</b>	CMD32GX4M4A2666C15(Ver4.23)(XMP)	32GB ( 4x 8GB )	DS	-	-	15-17-17-35	1.2V	•	•
<b>CORSAIR</b>	CMD32GX4M4A2666C15(Ver5.29)	32GB ( 4x 8GB )	DS	-	-	15-17-17-35	1.2V	•	•
<b>CORSAIR</b>	CMD32GX4M4A2666C16(Ver4.23)(XMP)	32GB ( 4x 8GB )	DS	-	-	16-18-18-35	1.2V	•	•
<b>CORSAIR</b>	CMK16GX4M4A2666C15(Ver4.23)(XMP)	16GB ( 4x 4GB )	SS	-	-	15-17-17-35	1.2V	•	•
<b>CORSAIR</b>	CMK16GX4M4A2666C15(Ver5.29)	16GB ( 4x 4GB )	SS	-	-	15-17-17-35	1.2V	•	•
<b>CORSAIR</b>	CMK16GX4M4A2666C16(Ver4.23)(XMP)	16GB ( 4x 4GB )	SS	-	-	16-18-18-35	1.2V	•	•
<b>CORSAIR</b>	CMK16GX4M4A2666C16(Ver5.29)(XMP)	16GB ( 4x 4GB )	SS	-	-	16-18-18-35	1.2V	•	•
<b>CORSAIR</b>	CMK32GX4M4A2666C15(Ver4.23)(XMP)	32GB ( 4x 8GB )	DS	-	-	15-17-17-35	1.2V	•	•
<b>CORSAIR</b>	CMK32GX4M4A2666C15(Ver5.29)(XMP)	32GB ( 4x 8GB )	DS	-	-	15-17-17-35	1.2V	•	•
<b>CORSAIR</b>	CMK32GX4M4A2666C16(Ver5.29)(XMP)	32GB ( 4x 8GB )	DS	-	-	16-16-18-35	1.2V	•	•
<b>CORSAIR</b>	CMK32GX4M4A2666C16R(Ver4.23)(XMP)	32GB ( 4x 8GB )	DS	-	-	16-18-18-35	1.2V	•	•
<b>CORSAIR</b>	CMK16GX4M2A2666C16	16GB (8GB*2)	DS	-	-	16-18-18-35	1.2	•	•
<b>CORSAIR</b>	CMD8GX4M2A2666C15	8GB (4GB*2)	SS	-	-	15-17-17-35	1.2	•	•
<b>CORSAIR</b>	CMK32GX4M2A2666C16	32GB (16GB*2)	DS	-	-	16-18-18-35	1.2	•	•
<b>CORSAIR</b>	CMD16GX4M2A2666C15	16GB (8GB*2)	DS	-	-	15-17-17-35	1.2	•	•
<b>Kingston</b>	HX426C15FBK2/8	8GB ( 2x 4GB )	SS	-	-	15-17-17-35	1.2	•	•
<b>Kingston</b>	HX426C15FBK4/16	16GB ( 4x 4GB )	SS	-	-	15-17-17-35	1.2		•
<b>Kingston</b>	HX426C15FBK2/16	16GB ( 2x 8GB )	DS	-	-	15-17-17-35	1.2	•	•
<b>Kingston</b>	HX426C15FBK4/32	32GB ( 4x 8GB )	DS	-	-	15-17-17-35	1.2		•
<b>G.SKILL</b>	F4-2666C15Q-16GRR(XMP)	16GB ( 4x 4GB )	SS	-	-	15-15-15-35	1.2V	•	•
<b>G.SKILL</b>	F4-2666C15Q-32GRR(XMP)	32GB ( 4x 8GB )	DS	-	-	15-15-15-35	1.2V	•	•
<b>G.SKILL</b>	F4-2666C16Q2-64GRB(XMP)	64GB ( 8x 8GB )	DS	-	-	16-16-16-36	1.2V	•	•
<b>ISDT</b>	IMA41GU6MFR8N-CF0(XMP)	8GB	DS	ISDT	I5AN4G8NMFR	15-15-15-35	1.2V		•
<b>ISDT</b>	IMA451U6MFR8N-CF0(XMP)	4GB	SS	ISDT	I5AN4G8NMFR	15-15-15-35	1.2V	•	•
<b>Team</b>	TCD44G2666C15ABK(XMP)	4GB	SS	Samsung	K4A4G085WD	15-15-15-35	1.2V	•	•
<b>Team</b>	TCD48G2666C15ABK(XMP)	32GB(4x 8GB)	DS	Team	TCD48G2666C15ABK	15-15-15-35	1.2V	•	•

**DDR4 2400 Qualified Vendors List (QVL)**

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
AVEXIR	AVD4U24001608G-4M	32GB (8 x 4GB)	DS	SK Hynix	H5AN4G8NMFRTFC	16-16-16-39	1.2V	•	•
CORSAIR	CMK16GX4M4A2400C14B	16GB (4 x 4GB)	SS	-	-	14-16-16-31	1.2V	•	•
CORSAIR	CMD16GX4M4A2400C14(Ver4.23)(XMP)	16GB (4 x 4GB)	SS	-	-	14-16-16-31	1.2V	•	•
CORSAIR	CMK16GX4M4A2400C14(Ver4.23)(XMP)	16GB (4 x 4GB)	SS	-	-	14-16-16-31	1.2V	•	•
Crucial	BLS4G4D240FSA.8FAD	4GB	SS	-	-	16-16-16-40	1.2V	•	•
crucial	BLS4G4D240FSA.8FAR(XMP)	4GB	SS	-	-	17-16-16-39	1.2V	•	•
Crucial	BLS8G4D240FSA.16FAD	8GB	DS	-	-	16-16-16-40	1.2V	•	•
Kingston	HX424C15FBK2/8	8GB ( 2x 4GB )	SS	-	-	15-15-15-35	1.2	•	
Kingston	HX424C15FBK4/16	16GB ( 4x 4GB )	SS	-	-	15-15-15-35	1.2		•
Kingston	HX424C15FBK2/16	16GB ( 2x 8GB )	DS	-	-	15-15-15-36	1.2	•	
Kingston	HX424C15FBK4/32	32GB ( 4x 8GB )	DS	-	-	15-15-15-37	1.2		•
Panram	PUD42400C154G4NJW	16GB (4 x 4GB)	SS	-	-	15-15-15-35	1.2V	•	•
Panram	PUD42400C158G4NJW	32GB (4 x 8GB)	DS	-	-	15-15-15-35	1.2V	•	•
Team	TED44GM2400C16BK	4GB	SS	Samsung	K4A4G085WD	16-16-16-39	1.2V	•	•
Team	TED48GM2400C16BK	8GB	DS	Samsung	K4A4G085WD	16-16-16-39	1.2V	•	•
V-color	TD4G8C17-UH	4GB	SS	V-color	DW3J0460HM	15-15-15-36	1.2V	•	•

**DDR4 2133 Qualified Vendors List (QVL)**

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								2 DIMM	4 DIMM
ADATA	AD4U2133W4G15-B	4GB	SS	SK Hynix	H5AN4G8NMFRTFC	15-15-15-36	-	•	•
ADATA	AD4U2133W8G15	8GB	DS	SK Hynix	H5AN4G8NMFRTFC	15-15-15-36	1.2V	•	•
Apacer	78.B1GM3.AF00B	4GB	SS	SK Hynix	H5AN4G8NMFRTFC	15-15-15-36	1.2V	•	•
Apacer	78.C1GM3.AF10B	8GB	DS	SK Hynix	H5AN4G8NMFRTFC	15-15-15-36	1.2V	•	•
AVEXIR	AVD4U21331504G-4M	4GB	SS	AVEXIR	512X8DDR4	15-15-15-35	1.2V	•	•
Century	CD8G-D4U2133	8GB	DS	SK Hynix	H5AN4G8NMFRTFC	15-15-15-36	-	•	•
CORSAIR	CMD16GX4M4B2133C10	16GB (4 x 4GB)	SS	-	-	10-12-12-31	1.35V	•	•
CORSAIR	CMK16GX4M4A2133C13(Ver4.23)(XMP)	16GB (4 x 4GB)	SS	-	-	13-15-15-28	1.2V	•	•
CORSAIR	CMK32GX4M4A2133C13(Ver4.23)(XMP)	32GB (4 x 8GB)	DS	-	-	13-15-15-28	1.2V	•	•
CORSAIR	CMK64GX4M8A2133C13(Ver4.23)(XMP)	64GB (8 x 8GB)	DS	-	-	13-15-15-28	1.2V	•	•
CORSAIR	CMV4GX4M1A2133C15	4GB	SS	-	-	15-15-15-36	1.2V	•	•
CORSAIR	CMV8GX4M1A2133C15	8GB	DS	-	-	15-15-15-36	1.2V	•	•
CORSAIR	CMV16GX4M1A2133C15	16GB	DS	-	-	15-15-15-36	1.2	•	•
CORSAIR	CMK32GX4M2A2133C13	32GB (16GB*2)	DS	-	-	13-15-15-28	1.2	•	•
G.SKILL	F4-2133C15Q-16GRR	16GB (4 x 4GB)	SS	-	-	15-15-15-35	1.2V	•	•
G.SKILL	F4-2133C15Q-32GRR	32GB (4 x 8GB)	DS	-	-	15-15-15-35	-	•	•
Kingston	HX421C14FBK2/8	8GB ( 2x 4GB )	SS	-	-	14-14-14-35	1.2	•	
Kingston	HX421C14FBK2/16	16GB ( 4x 4GB )	SS	-	-	14-14-14-35	1.2		•
Kingston	HX421C14FBK2/16	16GB ( 2x 8GB )	DS	-	-	14-14-14-35	1.2	•	
Kingston	HX421C14FBK4/32	16GB ( 4x 4GB )	DS	-	-	14-14-14-35	1.2		•
ISDT	IMA41GU6MFR8N-TF0	8GB	DS	ISDT	I5AN4G8NMFR	15-15-15-35	1.2V	•	•
ISDT	IMA451U6MFR8N-TF0	4GB	SS	ISDT	I5AN4G8NMFR	15-15-15-35	1.2V	•	•
Panram	PUD42133C134G4NJW	16GB (4 x 4GB)	SS	-	-	13-13-13-35	1.2V	•	•
Panram	PUD42133C138G4NJW	32GB (4 x 8GB)	DS	-	-	13-13-13-35	1.2V	•	•
Panram	PUD42133C154G2VS	8GB (2 x 4GB)	SS	SK Hynix	H5AN4GBNMFRTFC	15-15-15-36	1.2V	•	•
panram	PUD42133C154GNJK	4GB	SS	-	-	15-15-15-36	1.2V	•	•
Panram	PUD42133C158G2VS	16GB (2 x 8GB)	DS	SK Hynix	H5AN4GBNMFRTFC	15-15-15-36	1.2V	•	•
panram	PUD42133C158GNJK	8GB	DS	-	-	15-15-15-36	1.2V	•	•

SanMax	SMD-4G28HP-21P	4GB	SS	SK Hynix	H5AN4G8NMFRTFC	15-15-37-2	-	●	●
SanMax	SMD-8G28HP-21P	8GB	DS	SK Hynix	H5AN4G8NMFRTFC	15-15-37-2	-	●	●
SUPER TALENT	FBU2B008GM	8GB	DS	Micron	D9RGQ	15-15-15-36	1.2V	●	●
Team	TED44GM2133C15ABK	4GB	SS	SK Hynix	H5AN4G8NMFRTFC	15-15-15-36	1.2V	●	●
Transcend	TS1GLH64V1H	8GB	DS	Samsung	K4A4G085WD	15-15-15-37	-	●	●
Transcend	TS512MLH64V1H	4GB	SS	Samsung	K4A4G085WD	15-15-15-37	-	●	●
UMAX	84G44G93MC-21OMCALGF15	4GB	SS	Micron	D9RGQ	15-15-15-36	-	●	●
UMAX	84G48G93MC-21OMCGNGF15	8GB	DS	Micron	D9RGQ	15-15-15-36	-	●	●

#### 4 DIMM Slots

- **1 DIMM:** Supports one module inserted in any slot as Single-channel memory configuration. Install the module into A2 slot for better compatibility.
- **2 DIMM:** Supports one pair of modules inserted into the same color slots as one pair of Dual-channel memory configuration. Install the modules into A2/B2 slots for better compatibility.
- **4 DIMM:** Supports 4 modules inserted into both A1/A2 and B1/B2 slots as two pairs of Dual-channel memory configuration

-When running XMP at DDR4 3200 MHz or higher, the system's stability depends on the CPU's capabilities.

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value

-Always install DIMMs with the same CAS latency. For optimal compatibility, we recommend that you install memory modules of the same version or date code (D/C) from the same vendor. Check with the retailer to get the correct memory modules.

-Highly recommended to use 4-DIMM/2-DIMM kit for full DIMM configuration. Full DIMM support is subject to the physical characteristics of individual CPUs or Memory.

-Memory module with memory frequency higher than 2133 MHz and its corresponding timing or the loaded XMP Profile is not the JEDEC memory standard. The stability and compatibility of these memory modules depend on the CPU's capabilities and other installed devices.

-Always install DIMMs with the same CAS latency. For optimal compatibility, we recommend that you install memory modules of the same version or date code (D/C) from the same vendor. Check with the retailer to get the correct memory modules.