

P8Z77-M Memory Qualified Vendors List (QVL)

P8Z77-M Motherboard Qualified Vendors Lists (QVL)

DDR3 2400(O.C.) MHz capability

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)		
								1 DIMM	2 DIMM	4 DIMM
A-DATA	AX3U2400GC4G10(XMP)	4GB	DS	-	-	10-11-11-30	1.65	●	●	●
CORSAIR	CMGTX8(XMP)	8GB (4x 2GB)	SS	-	-	10-12-10-30	1.65	●	●	●
CORSAIR	CMGTX3(XMP)	2GB	DS	-	-	9-11-9-27	1.65	●	●	●
G.SKILL	F3-19200CL11Q-16GBZHD(XMP)	16GB (4x 4GB)	DS	-	-	11-11-11-31	1.65	●	●	●
G.SKILL	F3-19200CL11Q-16GBZHD(XMP)	16GB (4x 4GB)	DS	-	-	11-11-11-31	1.65	●	●	●
G.SKILL	F3-19200CL9Q-16GBZMD(XMP)	16GB (4x 4GB)	DS	-	-	9-11-11-31	1.65	●	●	●
G.SKILL	F3-19200CL10Q-32GBZHD(XMP)	32GB (4x 8GB)	DS	-	-	10-12-12-31	1.65	●	●	●
G.SKILL	F3-19200CL9D-4GBPIS(XMP)	4G (2x 2G)	DS	-	-	9-11-9-28	1.65	●	●	●
GEIL	GOC316GB2400C10QC(XMP)	16GB (4x 4GB)	DS	-	-	10-11-11-30	1.65	●	●	●
GEIL	GOC316GB2400C11QC(XMP)	16GB (4x 4GB)	DS	-	-	11-11-11-30	1.65	●	●	●
Kingston	KHX2400C11D3K4/8GX(XMP)	8GB (4x 2GB)	SS	-	-	11-13-11-30	1.65	●	●	●
Transcend	TX2400KLU-4GK (381850)(XMP)	2GB	DS	-	-	-	1.65	●	●	●
Transcend	TX2400KLU-4GK(374243)(XMP)	2GB	DS	-	-	-	1.65	●	●	●
Patriot	PPV34G2400C9K(XMP)	4GB (2x 2GB)	DS	-	-	9-11-9-27	1.66	●	●	●

* The 2400MHz memory modules above are supported by this motherboard; however, the actual frequency support varied depending on the O.C. margin of the installed CPU.

* Due to Intel® 2nd generation processors' behavior, DDR3 2200 and above/2000/1800 MHz memory module will run at DDR3 2133/1866/1600 MHz frequency as default.

4 DIMM :

• 1 DIMM: Supports one module inserted in any slot as Single-channel memory configuration

We suggest that you install the module into A2 slot for better stability.

• 2 DIMM: Supports one pair of modules inserted into either the blue slots or the black slots as one pair of Dual-channel memory configuration

We suggest that you install the module into A2B2 slot for better stability.

• 4 DIMM: Supports 4 modules inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.

P8Z77-M Motherboard Qualified Vendors Lists (QVL)

DDR3 2200(O.C.) MHz capability

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)		
								1 DIMM	2 DIMM	4 DIMM
G.SKILL	F3-17600CL7D-4GBFLS(XMP)	4G (2x 2G)	DS	-	-	7-10-10-28	1.65	●	●	●
GEIL	GET34GB2200C9DC(XMP)	4GB (2x 2GB)	DS	-	-	9-10-9-28	1.65	●	●	●
GEIL	GET38GB2200C9ADC(XMP)	8GB (2x 4GB)	DS	-	-	9-11-9-28	1.65	●	●	●

* The 2200MHz memory modules above are supported by this motherboard; however, the actual frequency support varied depending on the O.C. margin of the installed CPU.

* Due to Intel® 2nd generation processors' behavior, DDR3 2200 and above/2000/1800 MHz memory module will run at DDR3 2133/1866/1600 MHz frequency as default.

4 DIMM :

• 1 DIMM: Supports one module inserted in any slot as Single-channel memory configuration

We suggest that you install the module into A2 slot for better stability.

• 2 DIMM: Supports one pair of modules inserted into either the blue slots or the black slots as one pair of Dual-channel memory configuration

We suggest that you install the module into A2B2 slot for better stability.

• 4 DIMM: Supports 4 modules inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.

P8Z77-M Motherboard Qualified Vendors Lists (QVL)

DDR3 2133(O.C.) MHz capability

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)		
								1 DIMM	2 DIMM	4 DIMM
A-DATA	8154A 1044(XMP)	2GB	SS	-	-	9-9-9-24	1.55-1.75	●	●	●
A-DATA	AX3U2133C2G9B(XMP)	2GB	SS	-	-	9-11-9-27	1.55-1.75	●	●	●
A-DATA	AX3U2133GC2G9B(XMP)	2GB	SS	-	-	9-9-9-24	1.55-1.75	●	●	●
A-DATA	AX3U2133CG4G9B(XMP)	16GB (4x 4GB)	DS	-	-	9-11-9-27	1.65	●	●	●
Apacer	78.BAGE4.AFDOC(XMP)	8GB (2x 4GB)	DS	-	-	9-9-9-24	-	●	●	●
CORSAIR	CMT4GX3M2B2133C9(XMP)	4GB (2x 2GB)	DS	-	-	9-10-9-24	1.65	●	●	●
CORSAIR	CMT4GX3M2B2133C9(Ver7.1)(XMP)	4GB (2x 2GB)	DS	-	-	9-9-9-24	1.5	●	●	●
CORSAIR	CMT4GX3M2B2133C9(XMP)	4GB (2x 2GB)	DS	-	-	9-10-9-27	1.5	●	●	●
G.SKILL	F3-17000CL9Q-16GBXL(XMP)	16GB (4x 4GB)	DS	-	-	9-11-9-28	1.65	●	●	●
G.SKILL	F3-17000CL9Q-16GBZH(XMP)	16GB (4x 4GB)	DS	-	-	9-11-10-28	1.65	●	●	●
G.SKILL	F3-17066CL9Q-16GBTDD(XMP)	16GB (4x 4GB)	DS	-	-	9-9-9-24	1.65	●	●	●
G.SKILL	F3-17000CL11Q2-64GBZLD(XMP)	64GB (8x 8GB)	DS	-	-	11-11-11-30	1.5	●	●	●
G.SKILL	F3-17066CL9D-8GBPID(XMP)	8GB (2x 4GB)	DS	-	-	9-9-9-24	1.65	●	●	●
KINGSTON	KHX2133C11D3K4/16GX(XMP)	16GB (4x 4GB)	DS	-	-	11-12-11-30	1.65	●	●	●
KINGSTON	KHX2133C9AD3T1K2/4GX(XMP)	4GB (2x 2GB)	DS	-	-	-	1.65	●	●	●
KINGSTON	KHX2133C9AD3T1K2/4GX(XMP)	4GB (2x 2GB)	DS	-	-	9	1.65	●	●	●
KINGSTON	KHX2133C9AD3W1K2/4GX(XMP)	4GB (2x 2GB)	DS	-	-	9	1.65	●	●	●
KINGSTON	KHX2133C9AD3X2K2/4GX(XMP)	4GB (2x 2GB)	DS	-	-	9	1.65	●	●	●
KINGSTON	KHX2133C9AD3X2K2/4GX(XMP)	4GB (2x 2GB)	DS	-	-	9-9-9-24	1.65	●	●	●
KINGSTON	KHX2133C9AD3T1F4/8GX(XMP)	8GB (4x 2GB)	DS	-	-	9	1.65	●	●	●
OCZ	OCZ3XTEP2133C9L4GK	2GB	DS	-	-	7-7-7-20	1.65	●	●	●
Patriot	PPV34G2133C9K(XMP)	4GB (2x 2GB)	DS	-	-	9-11-9-27	1.66	●	●	●

4 DIMM :

• 1 DIMM: Supports one module inserted in any slot as Single-channel memory configuration

We suggest that you install the module into A2 slot for better stability.

• 2 DIMM: Supports one pair of modules inserted into either the blue slots or the black slots as one pair of Dual-channel memory configuration

We suggest that you install the module into A2B2 slot for better stability.

• 4 DIMM: Supports 4 modules inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.

P8Z77-M Motherboard Qualified Vendors Lists (QVL)

DDR3 2000(O.C.) MHz capability

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)		
								1 DIMM	2 DIMM	4 DIMM
A-DATA	AX3U2000GB2G9B(XMP)	2GB	DS	-	-	9-11-9-27	1.55-1.75	●	●	●
A-DATA	AX3U2000GC4G9B(XMP)	4GB	DS	-	-	9-11-9-27	1.55-1.75	●	●	●
Apacer	78.AAGD5.9KD(XMP)	6GB(3 x 2GB)	DS	-	-	9-9-9-27	-	●	●	●
CORSAIR	CMT6GX3M3A2000C8(XMP)	6GB (3x 2GB)	DS	-	-	8-9-8-24	1.65	●	●	●
G.SKILL	F3-16000CL9D-4GBRHH(XMP)	4GB(2 x 2GB)	DS	-	-	9-9-9-24	1.65	●	●	●
G.SKILL	F3-16000CL9D-4GBTDX(XMP)	4GB(2 x 2GB)	DS	-	-	9-9-9-24	1.65	●	●	●

GEIL	GUP34GB2000C9DC(XMP)	4GB (2x 2GB)	DS	-	-	9-9-9-28	1.65	●	●
KINGSTON	KHX2000C9AD3T1K3/6GX(XMP)	6GB (3x 2GB)	DS	-	-	9	1.65	●	●
Transcend	TX2000KLN-8GK (388375)(XMP)	4GB	DS	-	-	-	1.6	●	●
AEXEA	AXA3ES2G2000L G28V(XMP)	2GB	DS	-	-	-	1.65	●	●
AEXEA	AXA3ES4GK2000L G28V(XMP)	4GB (2x 2GB)	DS	-	-	-	1.65	●	●
Asint	SLA302G08-ML2HB(XMP)	4GB	DS	Hynix	H5TQ2G83BFRH9C	9-9-9-27	-	●	●
Gingle	FA3URSS673A801A	2GB	DS	-	-	9-9-9-24	-	●	●
Patriot	PX7312G2000ELK(XMP)	12GB (3x 4GB)	DS	-	-	9-11-9-27	1.65	●	●
Patriot	PV736G2000ELK(XMP)	6GB (3x 2GB)	DS	-	-	7-7-7-20	1.65	●	●
Silicon Power	SP002GBLYU200S02(XMP)	2GB	DS	-	-	-	-	●	●
Team	TXD32048M2000C9(XMP)	2GB	DS	Team	T3D1288RT-20	9-9-9-24	1.5	●	●
Team	TXD32048M2000C9-L(XMP)	2GB	DS	Team	T3D1288LT-20	9-9-9-24	1.5	●	●

4 DIMM :

• 1 DIMM: Supports one module inserted in any slot as Single-channel memory configuration

We suggest that you install the module into A2 slot for better stability.

• 2 DIMM: Supports one pair of modules inserted into either the blue slots or the black slots as one pair of Dual-channel memory configuration

We suggest that you install the module into A2B2 slot for better stability.

• 4 DIMM: Supports 4 modules inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.

P8Z77-M Motherboard Qualified Vendors Lists (QVL)

DDR3 1866(O.C.) MHz capability

Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)		
							1 DIMM	2 DIMM	4 DIMM
A-DATA	AX3U1866GC2G9B(XMP)	2GB	SS	-	-	9-11-9-27	1.55-1.75	●	●
A-DATA	AX3U1866GC4G9B(XMP)	4GB	DS	-	-	9-11-9-27	1.55-1.75	●	●
CORSAIR	CMT32GX3M4X1866C9(Ver1.50)(XMP)	32GB (4x 8GB)	DS	-	-	9-10-9-27	1.5	●	●
CORSAIR	CMT32GX3M4X1866C9(Ver3.23)(XMP)	32GB (4x 8GB)	DS	-	-	10-10-10-27	1.5	●	●
CORSAIR	CMT32GX3M4X1866C9(Ver3.23)(XMP)	32GB (4x 8GB)	DS	-	-	10-10-10-27	1.5	●	●
CORSAIR	CMZ32GX3M4X1866C10(Ver 3.23)(XMP)	32GB (4x 8GB)	DS	-	-	10-11-10-27	1.5	●	●
CORSAIR	CMZ8GX3M2A1866C9(XMP)	8GB (2x 4GB)	DS	-	-	9-10-9-27	1.5	●	●
Crucial	BLE4G3D1869DE1XT0_16FM(XMP)	4GB	DS	-	-	9-9-9-27	1.5	●	●
G.SKILL	F3-14900CL9Q-16GBXL(XMP)	16GB (4x 4GB)	DS	-	-	9-10-9-28	1.5	●	●
G.SKILL	F3-14900CL9Q-16GBZL(XMP)	16GB (4x 4GB)	DS	-	-	9-10-9-28	1.5	●	●
G.SKILL	F3-14900CL10Q2-64GBZLD(XMP)	64GB (8x 8GB)	DS	-	-	10-11-10-30	1.5	●	●
G.SKILL	F3-14900CL9QD-8GBSR(XMP)	8GB (2x 4GB)	DS	-	-	9-10-9-28	1.5	●	●
G.SKILL	F3-14900CL9QQ-8GBFLD(XMP)	8GB (2x 4GB)	DS	-	-	9-9-9-24	1.6	●	●
Patriot	PXD34G1866ELK(XMP)	4GB (2x 2GB)	SS	-	-	9-9-9-24	1.65	●	●
Patriot	PXD38G1866ELK(XMP)	8GB (2x 4GB)	DS	-	-	9-11-9-27	1.65	●	●
Team	TXD34096M1866HC9K-L(XMP)	4GB	DS	Hynix	H5TC2G83BFRH9A	9-11-9-27	1.65	●	●

4 DIMM :

• 1 DIMM: Supports one module inserted in any slot as Single-channel memory configuration

We suggest that you install the module into A2 slot for better stability.

• 2 DIMM: Supports one pair of modules inserted into either the blue slots or the black slots as one pair of Dual-channel memory configuration

We suggest that you install the module into A2B2 slot for better stability.

• 4 DIMM: Supports 4 modules inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.

P8Z77-M Motherboard Qualified Vendors Lists (QVL)

DDR3 1800(O.C.) MHz capability

Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)		
							1 DIMM	2 DIMM	4 DIMM
G.SKILL	F3-14400CL9D-4GBR(XMP)	4GB(2x 2GB)	DS	-	-	9-9-9-24	1.6	●	●

4 DIMM :

• 1 DIMM: Supports one module inserted in any slot as Single-channel memory configuration

We suggest that you install the module into A2 slot for better stability.

• 2 DIMM: Supports one pair of modules inserted into either the blue slots or the black slots as one pair of Dual-channel memory configuration

We suggest that you install the module into A2B2 slot for better stability.

• 4 DIMM: Supports 4 modules inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.

P8Z77-M Motherboard Qualified Vendors Lists (QVL)

DDR3 1600MHz capability

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)		
								1 DIMM	2 DIMM	4 DIMM
A-DATA	AM2U16BCP1	2GB	SS	A-DATA	3CCD-1509A	-	-	●	●	●
A-DATA	AM2U16BCP2	4GB	DS	A-DATA	3CCD-1509A	-	-	●	●	●
A-DATA	AX3U1600GC4G9(XMP)	4GB	DS	-	-	-	1.55-1.75	●	●	●
A-DATA	AX3U1600PC4G8(XMP)	4GB	DS	-	-	8-8-8-24	1.55-1.75	●	●	●
A-DATA	AX3U1600XC4G79(XMP)	4GB	DS	-	-	7-9-7-21	1.65	●	●	●
CORSAIR	CMZ8GX3M4X1600C9(Ver 2.12)(XMP)	8GB (4x 2GB)	SS	-	-	9-9-9-24	1.5	●	●	●
CORSAIR	HX3X12G1600C9(XMP)	12GB (6x 2GB)	DS	-	-	9-9-9-24	1.6	●	●	●
CORSAIR	CML16GX3M4X1600C8(Ver 2.12)(XMP)	16GB (4x 4GB)	DS	-	-	HeatSink Rearless	1.5	●	●	●
CORSAIR	CMZ16GX3M4A1600C9(XMP)	16GB (4x 4GB)	DS	-	-	9-9-9-24	1.5	●	●	●
CORSAIR	CMZ32GX3M4X1600C10 (Ver2.2)(XMP)	32GB (4x 8GB)	DS	-	-	10-10-10-27	1.5	●	●	●
CORSAIR	CMG4GX3M2A1600C6	4GB (2x 2GB)	DS	-	-	6-6-6-18	1.65	●	●	●
CORSAIR	CMP6GX3M3A1600C8(XMP)	6GB (3x 2GB)	DS	-	-	8-8-8-24	1.65	●	●	●
CORSAIR	CMP6GX3M3A1600C8(XMP)	6GB (3x 2GB)	DS	-	-	8-8-8-24	1.65	●	●	●
CORSAIR	CMX6GX3M3A1600C9(XMP)	6GB (3x 2GB)	DS	-	-	9-9-9-24	1.65	●	●	●
CORSAIR	CMX6GX3M3C1600C7(XMP)	6GB (3x 2GB)	DS	-	-	7-8-7-20	1.65	●	●	●
CORSAIR	CMZ8GX3M2A1600C8(XMP)	8GB (2x 4GB)	DS	-	-	8-8-8-24	1.5	●	●	●
CORSAIR	CMZ8GX3M2A1600C9(XMP)	8GB (2x 4GB)	DS	-	-	9-9-9-24	1.5	●	●	●
Crucial	BL12864BN1608.8F(XMP)	2GB(2x 1GB)	SS	-	-	8-8-8-24	1.65	●	●	●
Crucial	BL25664BN1608.16FF(XMP)	4GB(2x 2GB)	DS	-	-	8-8-8-24	1.65	●	●	●
Crucial	BLT4G3D1608DT1X0.16FM(XMP)	4GB	DS	-	-	8-8-8-24	1.5	●	●	●
G.SKILL	F3-12800CL7Q-16GBXH(XMP)	16GB (4x 4GB)	DS	-	-	7-8-7-24	1.6	●	●	●
G.SKILL	F3-12800CL9Q-16GBXL(XMP)	16GB (4x 4GB)	DS	-	-	9-9-9-24	1.5	●	●	●

G.Skill	F3-12800CL9Q-16GBZL(XMP)	16GB (4x 4GB)	DS	-	-	-	9-9-9-24	1.5	•	•	•
G.SKILL	F3-12800CL9D-4GBNQ(XMP)	4GB (2x 2GB)	DS	-	-	-	9-9-9-24	1.5	•	•	•
G.SKILL	F3-12800CL7D-8GBRH(XMP)	8GB (2x 4GB)	DS	-	-	-	7-8-7-24	1.6	•	•	•
G.SKILL	F3-12800CL7D-8GBXH(XMP)	8GB (2x 4GB)	DS	-	-	-	7-8-7-24	1.6	•	•	•
G.SKILL	F3-12800CL9D-8GBRL(XMP)	8GB (2x 4GB)	DS	-	-	-	9-9-9-24	1.5	•	•	•
G.SKILL	F3-12800CL8D-8GBECO(XMP)	8GB (2x 4GB)	DS	-	-	-	8-8-8-24	1.35	•	•	•
GEIL	GET316GB1600C9QC(XMP)	16GB (4x 4GB)	DS	-	-	-	9-9-9-28	1.6	•	•	•
GEIL	GUP34GB1600C7DC(XMP)	4GB (2x 2GB)	DS	-	-	-	7-7-7-24	1.6	•	•	•
GEIL	GVP38GB1600C8QC(XMP)	8GB (4x 2GB)	DS	-	-	-	8-8-8-28	1.6	•	•	•
KINGMAX	FLGE85F-C8KL9A(XMP)	2GB	SS	KINGMAX	N/A	-	9-9-9-28	-	•	•	•
KINGMAX	FLGF65F-C8KL9A(XMP)	4GB	DS	KINGMAX	N/A	-	9-9-9-28	-	•	•	•
KINGSTON	KHX1600C9D3K3/12GX(XMP)	12GB (3x 4GB)	DS	-	-	-	9	1.65	•	•	•
KINGSTON	KHX1600C9D3T1BK3/12GX(XMP)	12GB (3x 4GB)	DS	-	-	-	9	1.65	•	•	•
KINGSTON	KHX1600C9D3K3/12GX(XMP)	12GB (3x 4GB)	DS	-	-	-	-	1.65	•	•	•
Kingston	KHX1600C9D3K4/16GX(XMP)	16GB (4x 4GB)	DS	-	-	-	9-9-9-24	1.65	•	•	•
KINGSTON	KHX1600C9D3K6/24GX(XMP)	24GB (6x 4GB)	DS	-	-	-	9	1.65	•	•	•
Kingston	KHX1600C9D3K8/32GX(XMP)	32GB (8x 4GB)	DS	-	-	-	9-9-9-27	1.65	•	•	•
KINGSTON	KHX1600C9D3K2/4GX(XMP)	4GB (2x 2GB)	DS	-	-	-	-	1.65	•	•	•
KINGSTON	KHX1600C9D3LK2/4GX(XMP)	4GB (2x 2GB)	DS	-	-	-	-	1.35	•	•	•
KINGSTON	KHX1600C9D3X(2K2/4GX(XMP)	4GB (2x 2GB)	DS	-	-	-	-	9	1.65	•	•
Kingston	KVR16N11/4	4G	DS	Hynix	H5TQ2G83CFRPBC	-	-	1.5	•	•	•
KINGSTON	KHX1600C9D3K3/6GX(XMP)	6GB (3x 2GB)	DS	-	-	-	9	1.65	•	•	•
KINGSTON	KHX1600C9D3K3/6GX(XMP)	6GB (3x 2GB)	DS	-	-	-	9	1.65	•	•	•
KINGSTON	KHX1600C9D3K3/6GX(XMP)	6GB (3x 2GB)	DS	-	-	-	9	1.65	•	•	•
KINGSTON	KHX1600C9D3T1K3/6GX(XMP)	6GB (3x 2GB)	DS	-	-	-	9	1.65	•	•	•
Kingston	KHX1600C9D3LK2/8GX(XMP)	8GB (2x 4GB)	DS	-	-	-	9-9-9-24	1.35	•	•	•
KINGSTON	KHX1600C9D3P1K2/8G	8GB (2x 4GB)	DS	-	-	-	9	1.5	•	•	•
MICRON	MT8TF25664AZ-1G6M1	2GB	SS	MICRON	D9PFJ	-	-	-	•	•	•
MICRON	MT16KT51264AZ-1G6M1	4GB	DS	MICRON	D9PFJ	-	-	-	•	•	•
OCZ	OCZBE1600C8LV4GK	4GB (2x 2GB)	DS	-	-	-	8-8-8	1.65	•	•	•
OCZ	OCZ3OB1600LV4GK	4GB (2x 2GB)	DS	-	-	-	9-9-9	1.65	•	•	•
AMD	AES2G1609U1-U	2GB	SS	AMD	23EY4587MB6H	-	-	1.5	•	•	•
AMD	AE34G1609U2-U	4GB	DS	AMD	23EY4587MB6H	-	-	1.5	•	•	•
AMD	AP38G1608U2K(XMP)	8GB (2x 4GB)	DS	-	-	-	9-9-9-28	1.65	•	•	•
Asint	SLZ302G08-EGN1C	2GB	SS	ASint	302G08-GN1C	-	-	-	•	•	•
Asint	SLZ3128M8-EGJ1D(XMP)	2GB	DS	Asint	3128M8-GJ1D	-	-	-	•	•	•
Asint	SLA302G08-EGG1C(XMP)	4GB	DS	Asint	302G08-GG1C	9-9-9-27	-	-	•	•	•
Asint	SLA302G08-EGJ1C(XMP)	4GB	DS	Asint	302G08-GJ1C	9-9-9-27	-	-	•	•	•
Asint	SLA302G08-EGN1C	4GB	DS	Asint	302G08-GN1C	-	-	-	•	•	•
Asint	SLB304G08-EGN1B	8GB	DS	Asint	304G08-GN1B	-	-	-	•	•	•
ATP	AQ12M64B8BKK0S	4GB	DS	SAMSUNG	K4B2G08460	-	-	NO	•	•	•
EK Memory	EKM324L28BP8-I6(XMP)	4GB (2x 2GB)	DS	-	-	-	9	-	•	•	•
EK Memory	EKM324L28BP8-I16(XMP)	4GB (2x 2GB)	DS	-	-	-	9	-	•	•	•
Elixir	M2X2G64CB88G7N-DG(XMP)	2GB	SS	Elixir	N2CB2G80GN-DG	9-9-9-28	-	-	•	•	•
Elixir	M2X4G64CB8H1G5N-DG(XMP)	4GB	DS	Elixir	N2CB2G80GN-DG	9-9-9-28	-	-	•	•	•
Elixir	M2X8G64CB8HB5N-DG(XMP)	8GB	DS	Elixir	N2CB4G80BN-DG	9-9-9-28	1.5	-	•	•	•
GoodRam	GR1600D364L9/2G	2GB	DS	GoodRam	GF100BKC-JN	-	-	-	•	•	•
KINGTIGER	KTG2G1600PG3(XMP)	2GB	DS	-	-	-	-	-	•	•	•
Mushkin	996805(XMP)	4GB (2x 2GB)	DS	-	-	-	6-8-6-24	1.65	•	•	•
Mushkin	998805(XMP)	6GB (3x 2GB)	DS	-	-	-	6-8-6-24	1.65	•	•	•
Patriot	PX7312G1600LLK(XMP)	12GB (3x 4GB)	DS	-	-	-	8-9-8-24	1.65	•	•	•
Patriot	PGD316G1600ELK(XMP)	16GB (2x 8GB)	DS	-	-	-	-	1.65	•	•	•
Patriot	PGS34G1600LLKA	4GB (2x 2GB)	DS	-	-	-	8-8-8-24	1.7	•	•	•
Patriot	PGS34G1600LLKA	4GB (2x 2GB)	DS	-	-	-	7-7-7-20	1.7	•	•	•
Patriot	PGD38G1600ELK(XMP)	8GB (2x 4GB)	DS	-	-	-	9-9-9-24	1.65	•	•	•
Patriot	PPV38G1600LLK(XMP)	8GB (2x 4GB)	DS	-	-	-	8-9-8-24	1.65	•	•	•
SanMax	SMD-4G68HP-16KZ	4GB	DS	Hynix	H5TQ2G83BFRPBC	-	-	1.5	•	•	•
SanMax	SMD-4G68NG-16KZ	4GB	DS	ELPIDA	J2108BDBG-GN-F	-	-	-	•	•	•
Silicon Power	SP004GBLTU160V02(XMP)	4GB	DS	S-POWER	20YT5NG	9-9-9-24	1.5	-	•	•	•
Team	TXD31024M1600C8-D(XMP)	1GB	SS	Team	T3D1288RT-16	8-8-8-24	1.65	-	•	•	•
Team	TXD32048M1600HC8-D(XMP)	2GB	DS	Team	T3D1288RT-16	8-8-8-24	1.65	-	•	•	•
Team	TED34096M1600HC11	4GB	DS	Team	T3D2568ET-16	-	-	-	•	•	•
Team	TXD34096M1600HC9-D(XMP)	4GB	DS	Hynix	H5TC2G83BFRH9A	9-9-9-24	1.5	-	•	•	•

4 DIMM :

• 1 DIMM: Supports one module inserted in any slot as Single-channel memory configuration

We suggest that you install the module into A2 slot for better stability.

• 2 DIMM: Supports one pair of modules inserted into either the blue slots or the black slots as one pair of Dual-channel memory configuration

We suggest that you install the module into A2B2 slot for better stability.

• 4 DIMM: Supports 4 modules inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.

P8Z7-M Motherboard Qualified Vendors Lists (QVL)

DDR3 1333MHz capability

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)		
								1 DIMM	2 DIMM	4 DIMM
A-DATA	AD631B0823EV	2GB	SS	A-DATA	3CCA-1509A	-	-	•	•	•
A-DATA	AM2U139C2P1	2GB	SS	A-DATA	3CCD-1509A	-	-	•	•	•
A-DATA	ADXD133GC2G9(XMP)	2GB	SS	-	-	9-9-9-24	1.25-1.35	•	•	•
A-DATA	AD631C1624EV	4GB	DS	A-DATA	3CCA-1509A	-	-	•	•	•
A-DATA	AM2U139C4P2	4GB	DS	A-DATA	3CCD-1509A	-	-	•	•	•
A-DATA	SU3U1333W8G9(XMP)	8GB	DS	ELPIDA	J4208BA-SE-DJ-F	-	-	•	•	•
Apacer	78.A1GC6.9L1	2GB	DS	Apacer	AM5D5808FEQSBG	9	-	•	•	•
Apacer	78.B1GDE.9L10C	4GB	DS	Apacer	AM5D5908CEHSBG	9	-	•	•	•
CORSAIR	TW3X4G1333C9A	4GB (2x 2GB)	DS	-	-	9-9-9-24	1.5	•	•	•
CORSAIR	CMX8GX3M2A1333C9(XMP)	8GB (2x 4GB)	DS	-	-	9-9-9-24	1.5	•	•	•
G.SKILL	F3-10600CL9D-4GBNT	4GB (2x 2GB)	DS	G.SKILL	D3 128M8CE9 2GB	9-9-9-24	1.5	•	•	•
G.SKILL	F3-10666CL8D-4GBHK(XMP)	4GB (2x 2GB)	DS	-	-	8-8-8-21	1.5	•	•	•
G.SKILL	F3-10666CL7D-8GBRH(XMP)	8GB (2x 4GB)	DS	-	-	7-7-7-21	1.5	•	•	•
G.SKILL	F3-10666CL9D-8GBRL	8GB (2x 4GB)	DS	-	-	9-9-9-24	1.5	•	•	•
G.SKILL	F3-10666CL9D-8GBXL	8GB (2x 4GB)	DS	-	-	9-9-9-24	1.5	•	•	•
GEIL	GET316GB1333C9QC	16GB (4x 4GB)	DS	-	-	9-9-9-24	1.5	•	•	•
GEIL	GG34GB1333C9DC	4GB (2x 2GB)	DS	GEIL	GL1L128M88BA11FW	9-9-9-24	1.3	•	•	•
GEIL	GG34GB1333C9DC	4GB (2x 2GB)	DS	GEIL	GL1L128M88BA15B	9-9-9-24	1.3	•	•	•
GEIL	GB34GB1333C7DC	4GB (2x 2GB)	DS	GEIL	GL1L128M88BA15FW	7-7-7-24	1.5	•	•	•
GEIL	GVP38GB1333C9DC	8GB (2x 4GB)	DS	-	-	9-9-9-24	1.5	•	•	•

GEIL	GVP38GB1333C7QC	8GB (4x 2GB)	DS	-	7-7-7-24	1.5	•	•
Hynix	HMT125U6TFR8A-H9	2GB	DS	Hynix	H5TC1G83TFR	-	•	•
KINGMAX	FLFD45F-B8KL9	1GB	SS	KINGMAX	KFB8FNLFX-BNF-15A	-	•	•
KINGMAX	FLFE85F-C8KL9	2GB	SS	KINGMAX	KFC8FNLBG-GXX-12A	-	•	•
KINGMAX	FLFE85F-C8KL9	2GB	SS	KINGMAX	KFC8FNLFX-DXX-15A	-	•	•
KINGMAX	FLFE85F-C8KL9	2GB	DS	KINGMAX	KFB8FNLFX-BXX-15A	-	•	•
KINGMAX	FLFF65F-C8KL9	4GB	DS	KINGMAX	KFC8FNLFB-GXX-12A	-	•	•
KINGMAX	FLFF65F-C8KL9	4GB	DS	KINGMAX	KFC8FNLFX-DXX-15A	-	•	•
KINGMAX	FLFF65F-C8KL9	4GB	DS	Kingmax	KFC8FNMXF-BXX-15A	-	•	•
KINGSTON	KVR1333D3S8N9/2G	2GB	SS	Micron	IFD77 D9L GK	-	1.5	•
KINGSTON	KVR1333D3N9/2G(矮版)	2GB	DS	Elpida	J1108BDDBG-DJ-F	-	1.5	•
KINGSTON	KVR1333D3N9/2G	2GB	DS	Kingston	D1288JPNDPLD9U	9	1.5	•
KINGSTON	KVR1333D3N9K2/4G	4GB (2x 2GB)	DS	KINGSTON	D1288JEMFPGD9U	-	1.5	•
KINGSTON	KVR1333D3E9S/4G	4GB	DS	Elpida	J2108ECSE-DJ-F	9	1.5	•
KINGSTON	KVR1333D3NH/8G	8GB	DS	ELPIDA	J4208EASE-DJ-F	9-9-9-24	1.5	•
MICRON	MT8JTF25664AZ-1G4M1	2GB	SS	MICRON	D9PFJ	-	•	•
OCZ	OCZ3G1333LV4GK	4GB (2x 2GB)	DS	-	-	9-9-9	1.65	•
OCZ	OCZ3G1333LV8GK	8GB (2x 4GB)	DS	-	-	9-9-9	1.65	•
OCZ	OCZ3G1333LV8GK	8GB (2x 4GB)	DS	-	-	9-9-9	1.65	•
OCZ	OCZ3RPR1333C9LV8GK	8GB (2x 4GB)	DS	-	-	9-9-9	1.65	•
SAMSUNG	M378B5673FH0-CH9	2GB	DS	SAMSUNG	K4B1G0846F	-	•	•
SAMSUNG	M378B5273CH0-CH9	4GB	DS	SAMSUNG	K4B2G0846C	K4B2G0846C	-	•
SAMSUNG	M378B1G73AH0-CH9	8GB	DS	SAMSUNG	K4B4G0846A-HCH9	-	•	•
ACTICA	ACT1GHU64B8F1333S	1GB	SS	SAMSUNG	K4B1G0846F	-	•	•
ACTICA	ACT1GHU72C8G1333S	1GB	SS	SAMSUNG	K4B1G0846F(ECC)	-	•	•
ACTICA	ACT2GHU64B8G1333M	2GB	DS	Micron	D9KPT	-	•	•
ACTICA	ACT2GHU64B8G1333S	2GB	DS	SAMSUNG	K4B1G0846F	-	•	•
ACTICA	ACT2GHU72D8G1333M	2GB	DS	Micron	D9KPT(ECC)	-	•	•
ACTICA	ACT2GHU72D8G1333S	2GB	DS	SAMSUNG	K4B1G0846F(ECC)	-	•	•
ACTICA	ACT4GHU64B8H1333H	4GB	DS	Hynix	H5TQ2G83AFR	-	•	•
ACTICA	ACT4GHU72D8H1333H	4GB	DS	Hynix	H5TQ2G83AFR(ECC)	-	•	•
AMD	A3E2G1339J1-U	2GB	SS	AMD	23EY4587MB3H	-	1.5	•
AMD	AE34G1339U2-U	4GB	DS	AMD	23EY4587MB3H	-	1.5	•
Asint	SLA302G08-EDJ1C	2GB	SS	Asint	302G08-DJ1C	-	•	•
Asint	SLZ302G08-EDJ1C	4GB	DS	Asint	302G08-DJ1C	-	•	•
ATP	AQ12MT72E8BKH9S	4GB	DS	SAMSUNG	K4B2G0846C(ECC)	-	•	•
BUFFALO	D3U1333-1G	1GB	SS	Elpida	J1108BFBG-DJ-F	-	•	•
BUFFALO	D3U1333-2G	2GB	DS	Elpida	J1108BFBG-DJ-F	-	•	•
BUFFALO	D3U1333-4G	4GB	DS	NANYA	NT5CB256M8BN-CG	-	•	•
EK Memory	EKM324L28BP8-I13	4GB(2x 2GB)	DS	-	-	9	-	•
Elixir	M2F2G64C688D7N-CG	2GB	SS	Elixir	M2CB2G80DN-CG	-	•	•
GoodRam	GR1333D364L9/2G	2GB	DS	Qimonda	IDSH1G-03A1F1C-13H	-	•	•
INNODISK	M3UN-2GHJBC09	2GB	SS	Hynix	H5TQ2G83CFRH9C	9-9-9-24	•	•
INNODISK	M3UN-4GHJAC09	4GB	DS	Hynix	H5TQ2G83CFRH9C	9-9-9-24	•	•
KINGTIGER	F10DA2T1680	2GB	DS	KINGTIGER	KTG1333PS1208NST-C9	-	•	•
KINGTIGER	KTG2G1333PG3	2GB	DS	-	-	-	•	•
Mach Xtreme	MXD3V13332GS	2GB	SS	Mach Xtreme	C2S46D30-D313	-	•	•
Mach Xtreme	MDX3U133316GQ	16GB (4x 4GB)	DS	-	-	-	•	•
Patriot	PGD316G1333ELK(XMP)	16GB (2x 8GB)	DS	-	-	9-9-9-24	1.5	•
Patriot	PSD32G13332	2GB	DS	Prriot	PM128MBD3BU-15	9	-	•
Patriot	PGS34G1333LLKA	4GB(2x 2GB)	DS	-	-	7-7-7-20	1.7	•
Patriot	PG38G1333EL(XMP)	8GB	DS	-	-	-	1.5	•
RiDATA	C304627CB1AG22Fe	2GB	DS	RiDATA	C304627CB1AG22Fe	9	-	•
RiDATA	E304459CB1AG32Cl	4GB	DS	RiDATA	E304459CB1AG32Cl	9	-	•
Silicon Power	SP001GBLTE133S01	1GB	SS	NANYA	NT5CB128M8AN-CG	-	•	•
Silicon Power	SP001GBLTU133S02	1GB	SS	S-POWER	10YT3E5	9	-	•
Silicon Power	SP002GBLTE133S01	2GB	DS	NANYA	NT5CB128M8AN-CG	-	•	•
Silicon Power	SP004GBLTE133V02	4GB	DS	S-POWER	20YT3NG	9-9-9-24	-	•
Team	TXD32048M1333C7-D(XMP)	2GB	DS	Team	T3D1288LT-13	7-7-7-21	1.5-1.6	•
Team	TED34096M1333HC9	4GB	DS	Team	T3D2568LT-13	-	-	•

4 DIMM :

* **1 DIMM:** Supports one module inserted in any slot as Single-channel memory configuration

We suggest that you install the module into A2 slot for better stability.

* **2 DIMM:** Supports one pair of modules inserted into either the blue slots or the black slots as one pair of Dual-channel memory configuration

We suggest that you install the module into A2B2 slot for better stability.

* **4 DIMM:** Supports 4 modules inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.