

AM1I-A

DDR3 1333 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	ocket support (O	
								1 DIMM	2 DIMM
KINGSTON	KVR1333D3N9/4G	4GB	SS	KTC	D2568JENCNGD9U	9-9-9-24-33	1.5V	●	●
ASint	SLA304G08-EDJ6A	4GB	SS	ASINT	304G08-DJ6A	9-9-9-24-33	1.5V	●	●
ASint	SLA304G08-EDJ6B	4GB	SS	ASINT	304G08-DJ6B	9-9-9-24-33	1.5V	●	●
MUSHKIN	PC3-10666	4GB	SS	N/A	Heat-Sink Package	9-9-9-24	1.50V	●	●
MUSHKIN	PC3-10600	2GB	SS	SEC 410 HC15	K4W2GO846P	9-9-9-24	1.50V	●	●
SMART	SH5126UD325893HE	4GB	DS	SEC 343 BYKO	K4B2GO8460	9-9-9-24-33	1.5V	●	●
SMART	SH5126UD325893SQ	4GB	DS	SEC 343 BYKO	K4B2GO8460	9-9-9-24-33	1.5V	●	

2 DIMM Slots

- **1 DIMM**: Supports one module inserted in any slot as Single-channel memory configuration
- **2 DIMM**: Supports 2 modules inserted into both the **blue** or **black** slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.

AM1I-A

DDR3 1600 Qualified Vendors List (QVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	Socket support (O	
								1 DIMM	2 DIMM
CRUCIAL	CT102464BA160B.C16FED	8GB	DS	CRUCIAL	CT512X8-160B		1.50V	•	
G.SKILL	F3-1600C11S-4GNT	4GB	SS	SEC 343 XYKO	K4B4GO846D	11-11-11-28	1.5V	•	•
KINGMAX	FLGE85F-B6HYB	2GB	SS	HYNIX	H5TQ2G63FFR		1.50V	•	•
KINGSTON	KVR16N11S/4	4GB	SS	KINGSTON	D5128EC4BPGGBU		1.5V	•	
KINGSTON	KVR16N11/4	4GB	SS	KINGSTON	D5128EC4BPGGBU		1.35V	•	•
KINGSTON	KVR16N11/4	4GB	SS	KINGSTON	D5128EC4BPGGBU		1.5V	•	•
MUSHKIN	PC3-12800	4GB	DS	N/A	Heat-Sink Package	9-9-9-24	1.50V	•	•
MUSHKIN	PC3-12800	4GB	DS	N/A	Heat-Sink Package	9-9-9-24	1.50V	•	•
MIRA	PLAF8L93B-GN2	8GB	DS	N/A	BJE159C3G-M	9-9-9-24	1.50V	•	•
Transcend	TS512MLK64W6H	4GB	SS	SEC 343 XYKO	K4B4GO846D	11-11-11-28-39	1.35V	•	•
Transcend	TS1GLK64W6H	8GB	DS	SEC 343 XYKO	K4B4GO846D	11-11-28-39	1.35V	•	•
TEAM	TLD38G1600HC9BK	8GB	DS	-	-	9-9-9-24	1.5V	•	•
TEAM	TED34GM1600C11BK	4GB	DS	HYNIX	H5TQ2G83CFY	11-11-11-28	1.5V	•	
ADATA	N/A	4GB	SS	ADATA	3WCD-12IIA EL1348V	-	-	•	•
ASint	SLA304G08-EGN6A	4GB	SS	ASINT	304G08-GN6A	11-11-11-28-39	1.5V	•	•
ASint	SLA304G08-EGN6B	4GB	SS	ASINT	304G08-GN6B	11-11-11-28-39	1.5V	•	•
AVEXIR	AVD3U16000904G-4CI	4GB	SS	N/A	N/A		1.5V	•	•
AVEXIR	AVD3U16001008G-4CI	8GB	DS	N/A	N/A		1.5V	•	•
PANRAM	PUD31600C114GPSB	4GB	SS	N/A	N/A	11-11-28-39	1.5V	•	•
PANRAM	PUD31600C118GPSB	8GB	DS	DS	N/A	11-11-28-39	1.5V	•	•
SAMSUNG	M379B5273DHO-YKO 1325	4GB	DS	SEC 312 BJKO	J4208BBBG-GN-F	11-11-28-39	1.35V	•	•
VENTURA	D3-55DK1145V-11	2GB	SS	SEC 404 BCKO	K4B2GO846Q	11-11-44-28-39	1.5V	•	•

2 DIMM Slots

- **1 DIMM:** Supports one module inserted in any slot as Single-channel memory configuration
- **2 DIMM:** Supports 2 modules inserted into both the **blue** or **black** slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.