

Qualified Vendors List (QVL) Standard table for user manual

Project Name:

Size	Vendor	Chip No.	CL	Chip Brand	SS/DS	Part No.	DIMM socket support (Optional)		
							A*	B*	C*
DDR2 800 512MB	KINGSTON	Heat-Sink Package	N/A	N/A	SS	KHX6400D2/512	V	V	
DDR2 800 512MB	KINGSTON	K4T51083QC	N/A	N/A	SS	KVR800D2N5/512			
DDR2 800 1024MB	KINGSTON	K4T51083QC	N/A	N/A	DS	KVR800D2N5/1G		V	V
DDR2 800 256MB	SAMSUNG	K4T56083QF-ZCE7	N/A	N/A	SS	M378T3253FZ3-CE7	V	V	
DDR2 800 256MB	SAMSUNG	K4T56083QF-ZCE7(ECC)	N/A	N/A	SS	M391T3253FZ3-CE7			
DDR2 800 512MB	SAMSUNG	EDD339XX	N/A	N/A	SS	M378T6553CZ3-CE7	V	V	
DDR2 800 512MB	Infineon	HYB18T256800AF25	N/A	N/A	DS	HYS64T64520HU-2.5-A	V	V	V
DDR2 800 512MB	Hynix	HY5PS12821AFP-S6	N/A	N/A	SS	HYMP564U64AP8-S6			
DDR2 800 1024MB	Hynix	HY5PS12821AFP-S6	N/A	N/A	DS	HYMP512U64AP8-S6			
DDR2 800 512MB	MICRON	5JAHZ9DQQ	N/A	N/A	SS	MT8HTF6464AY-80EA3	V	V	V
DDR2 800 1024MB	MICRON	5JAHZ9DQQ	N/A	N/A	DS	MT16HTF12864AY-80EA3	V	V	V
DDR2 800 512MB	CORSAIR	Heat-Sink Package	N/A	N/A	SS	CM2X512A-6400			
DDR2 800 1024MB	CORSAIR	Heat-Sink Package	N/A	N/A	DS	CM2X1024-6400PRO	V	V	V
DDR2 800 256MB	A-DATA	E2508AB-GE-E	N/A	N/A	SS	M20EL6F3G3170A1D0Z	V	V	
DDR2 800 256MB	A-DATA	E2508AB-GE-E	N/A	N/A	SS	M20EL6F3G3160A1D0Z			
DDR2 800 256MB	A-DATA	E2508AB-GE-E	N/A	N/A	SS	M20EL6F3G3160A1D0Z	V		
DDR2 800 512MB	A-DATA	E2508AB-GE-E	N/A	N/A	DS	M20EL6F3H4170A1D0Z			
DDR2 800 256MB	Apacer	E2508AB-GE-E	N/A	N/A	SS	78.81091.420	V	V	
DDR2 800 512MB	Apacer	E2508AB-GE-E	N/A	N/A	DS	78.91091.420			
DDR2 800 512MB	Crucial	Heat-Sink Package	N/A	N/A	SS	BL6464AA804.8FA			
DDR2 800 1024MB	Crucial	Heat-Sink Package	N/A	N/A	DS	BL12864AA804.16FA		V	
DDR2 800 256MB	TwinMOS	E2508AB-GE-E	N/A	N/A	SS	8G-24IK2-EBT			
DDR2 800 512MB	OCZ	Heat-Sink Package	N/A	N/A	SS	OCZ28001024EBDCPE-K			
DDR2 800 512MB	Elixir	N2TU51280AE-25C	N/A	N/A	SS	M2Y51264TU88A2B-25C			
DDR2 800 512MB	NANYA	NT5TU64M8AE-25C	N/A	N/A	SS	NT512T64U88A1BY-25C			
DDR2 800 512MB	NANYA	NT5TU64M8BE-25C	N/A	N/A	SS	NT512T64U88B0BY-25C			
DDR2 800 1024MB	NANYA	NT5TU64M8BE-25C	N/A	N/A	DS	NT1GT64U8HB0BY-25C			

Note:

A* : Supports one module inserted in any slot as Single-channel memory configuration

B* : Supports one pair of modules inserted into either the blue slots or the black slots as one pair of Dual-channel memory configuration

C* : Supports 3 modules inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

